

NEUCOR CORES

NEUCOR CORES are made with NAF resin				NEUCOR CORES are exempt from CARB ATCM 93120			
Standard Width & Length - 49" X 97"				Width & Length Tolerance $\pm 1/16"$			
Squareness $\pm 1/8"$		Thickness Tolerance $\pm 0.005"$		Thickness Swell $\leq 12\%$			
Available NEUCOR CORES		1/2"		7/8"			
Thickness (in)		0.500"		0.875"			
Weight (lbs)		23.5		23.5			
Flat Crush (psi)		300		150			

NEUCOR PANELS

All surface materials used in NEUCOR PANELS are CARB compliant, NAF available on request.

Standard Width & Length - 49" X 97"				Width & Length Tolerance $\pm 1/16"$			
Squareness $\pm 1/8"$		Thickness Tolerance $\pm 0.005"$		Thickness Swell $\leq 12\%$			
Thickness (in)	MOE (psi)	MOR (psi)		Flat Crush	Weight (lbs)	Density (lbs/ft ³)	
3/4	350,000	2,100		300	62.2	30.1	
1	350,000	2,100		300	100.3	36.5	
1 1/8	350,000	2,100		150	62.2	20.1	
1 1/4	350,000	2,100		150	86.2	25	
1 1/2	350,000	2,100		300	124.3	30.1	
2	350,000	2,100		150	86.2	15.7	
3	350,000	2,100		150	129.2	15.7	